


Features

- Operating voltage : 5.0V, 5.4V, 7.5V
- 60/70°C 1,000h, · Pb Free and RoHS Compliant



Applications


- Less than 100mA from sec to hours
- Tax controller, Handy terminal, Bar-cord banner, GPS,
- Gas & Water meter, Digital camera, Container Tracking System

Specifications

Items	Characteristics			
Rated working voltage	5.0(5.4) VDC		7.5 VDC	
Operating temperature	-25 to +70°C	-40 to +65°C	-25 to +70°C	-40 to +65°C
Nominal Cap. range	0.5F to 7.5F		0.33F to 5.0F	
Capacitance tolerance	-20% to +40%(at 25°C)			
Endurance	After 1,000 hours Application of rated DC working voltage at +65/70°C, the capacitor shall meet the following limits. <ul style="list-style-type: none"> • Capacitance change : ≤30% of initial value • Internal resistance change : ≤100% of spec. value 			
Projected Cycle Life*	500,000 Cycles			
	1 Cycle : Charge-Discharge between V_{rated} and $1/2V_{rated}$ <ul style="list-style-type: none"> • Capacitance change : ≤30% of initial value • Internal resistance change : ≤100% of spec. value 			
Shelf life	2 Years (Storage in Operating temp. range above for each products without electrical load) <ul style="list-style-type: none"> • Capacitance change : ≤10% of initial value • Internal resistance change : ≤50% of initial value 			

* Cycle life varies according to the condition of application i.e. charge-discharge condition including current, temperature, voltage range and etc.

Shape of Standard Product



Standard Products and Dimensions (not to scale)

Part number	Operating Voltage(V)	Operating temperature	Capacitance (F)	ESR (Ω , @1kHz)	W x L x H (mm)	F (mm)	
DRMH 5R0 504	5.0V	-25 ~ 70°C	0.5	≤ 0.600	16.5 X 8.0 X 14.0	5.0/12.0	
DRMH 5R0 155			1.5	≤ 0.300	16.5 X 8.0 X 21.0	5.0/12.0	
DRMH 5R0 255R			2.5	≤ 0.240	16.5 X 8.0 X 26.0	5.3/12.3	
DRMH 5R0 255S			2.5	≤ 0.240	20.5 X 10.0 X 21.0	5.3/15.3	
DRMH 5R0 355L			3.5	≤ 0.200	16.5 X 8.0 X 31.0	5.0/12.0	
DRMH 5R0 355R			3.5	≤ 0.200	20.5 X 10.0 X 21.0	5.3/15.3	
DRMH 5R0 355D			3.5	≤ 0.200	20.5 X 10.0 X 26.0	5.3/15.3	
DRMH 5R0 505R			5.0	≤ 0.150	20.5 X 10.0 X 26.0	5.3/15.3	
DRMH 5R0 505RX			5.0	≤ 0.150	20.5 X 10.0 X 31.0	5.3/15.3	
DRMH 5R0 505S			5.0	≤ 0.150	25.5 X 12.5 X 21.0	7.8/17.8	
DRMH 5R0 755			7.5	≤ 0.110	25.5 X 12.5 X 26.0	7.8/17.8	
DRML 5R4 504			5.4V	-40 ~ 65°C	0.5	≤ 0.600	16.5 X 8.0 X 14.0
DRML 5R4 155	1.5	≤ 0.300			16.5 X 8.0 X 21.0	5.0/12.0	
DRML 5R4 255R	2.5	≤ 0.240			16.5 X 8.0 X 26.0	5.0/12.0	
DRML 5R4 255S	2.5	≤ 0.240			20.5 X 10.0 X 21.0	5.3/15.3	
DRML 5R4 355L	3.5	≤ 0.200			16.5 X 8.0 X 31.0	5.0/12.0	
DRML 5R4 355R	3.5	≤ 0.200			20.5 X 10.0 X 21.0	5.3/15.3	
DRML 5R4 355D	3.5	≤ 0.200			20.5 X 10.0 X 26.0	5.3/15.3	
DRML 5R4 505R	5.0	≤ 0.150			20.5 X 10.0 X 26.0	5.3/15.3	
DRML 5R4 505RX	5.0	≤ 0.150			20.5 X 10.0 X 31.0	5.3/15.3	
DRML 5R4 505S	5.0	≤ 0.150			25.5 X 12.5 X 21.0	7.8/17.8	
DRML 5R4 755	7.5	≤ 0.110			25.5 X 12.5 X 26.0	7.8/17.8	
DRMH 7R5 334	7.5V	-25 ~ 70°C			0.33	≤ 0.900	25.0 X 8.0 X 14.0
DRMH 7R5 105			1.0	≤ 0.450	25.0 X 8.0 X 21.0	13.5	
DRMH 7R5 155R			1.5	≤ 0.360	25.0 X 8.0 X 26.0	13.5	
DRMH 7R5 155S			1.5	≤ 0.360	31.0 X 10.0 X 21.0	15.6	
DRMH 7R5 205R			2.0	≤ 0.300	31.0 X 10.0 X 21.0	15.6	
DRMH 7R5 205D			2.0	≤ 0.300	31.0 X 10.0 X 26.0	15.6	
DRMH 7R5 305R			3.0	≤ 0.250	31.0 X 10.0 X 26.0	15.6	
DRMH 7R5 305RX			3.0	≤ 0.250	31.0 X 10.0 X 31.0	15.6	
DRMH 7R5 305S			3.0	≤ 0.250	38.5 X 12.5 X 21.0	20.6	
DRMH 7R5 505			5.0	≤ 0.150	38.5 X 12.5 X 26.0	20.6	
DRML 7R5 334			-40 ~ 65°C	0.33	≤ 0.900	25.0 X 8.0 X 14.0	13.5
DRML 7R5 105				1.0	≤ 0.450	25.0 X 8.0 X 21.0	13.5
DRML 7R5 155R		1.5		≤ 0.360	25.0 X 8.0 X 26.0	13.5	
DRML 7R5 155S		1.5		≤ 0.360	31.0 X 10.0 X 21.0	15.6	
DRML 7R5 205R		2.0		≤ 0.300	31.0 X 10.0 X 21.0	15.6	
DRML 7R5 205D		2.0		≤ 0.300	31.0 X 10.0 X 26.0	15.6	
DRML 7R5 305R		3.0		≤ 0.250	31.0 X 10.0 X 26.0	15.6	
DRML 7R5 305RX		3.0		≤ 0.250	31.0 X 10.0 X 31.0	15.6	
DRML 7R5 305S		3.0		≤ 0.250	38.5 X 12.5 X 21.0	20.6	
DRML 7R5 505		5.0		≤ 0.150	38.5 X 12.5 X 26.0	20.6	

Note : It is not allowed to go through reflow (IR, Atmosphere heating methods etc.) process